

SECTION1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product code : B/W KIT INVERSIONE SBIANCA Permanganato PARTE B LT 1
Trades code : B/W KIT INV BL B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Photographic Process

Sectors of use:

Professional use[SU22]

Product category:

Photochemicals

Process categories:

Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)[PROC5]

Uses advised against

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

BELLINI FOTO S.r.l.

VIA FERRIERA, 68 - 06089 - TORGIANO - PERUGIA

ITALY

Tel +39 075 985 174 Fax +39 075 985 288

E-mail:info@bellinifoto.it - Web: www.bellinifoto.it

E-mail technical assistance: enrico.pompili@bellinifoto.it

Produced by

BELLINI FOTO S.r.L.

Via Ferriera, 68 06089 TORGIANO - PG - ITALY Tel. +39 075 985174

1.4. Emergency telephone number

Bellini Foto S.r.l. (PG) - Tel . +39 075 985 174

SECTION2. Hazards identification

2.1. Classification of the substance or mixture

CAS 7664-93-9 CEE 016-020-00-8 EINECS 231-639-5 REACH 01-2119458838-20

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS05

Hazard Class and Category Code(s):

Skin Corr. 1, Eye Dam. 1

Hazard statement Code(s):

H314 - Causes severe skin burns and eye damage.

H318 - Causes serious eye damage.

Corrosive product: causes severe skin burns and eye damage.

If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):

GHS05 - Danger

Hazard statement Code(s):

H314 - Causes severe skin burns and eye damage.

Supplemental Hazard statement Code(s):



not applicable

Precautionary statements:

Prevention

P260 - Do not breathe dust, fume, gas, mist, vapours, spray.

P264 - Thoroughly wash clothing after use.

P280 - Wear protective gloves protective clothing eye protection face protection.

Response

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a doctor if symptoms persist

Disposal

P501 - Dispose of contents and container in accordance with the laws in force

Contains:

Sulphuric acid 36 %

2.3. Other hazards

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII
The use of this chemical agent involves the obligation of "risk assessment" by the employer in accordance with Dlgs. April 9, 2008 # 81. Workers exposed to this chemical agent should not be subjected to health surveillance if the results of the risk assessment show that, in relation to the type and quantity of hazardous chemical agent and that agent exposure frequency and mode, you just a "moderate risk" for the health and safety of workers and that the measures laid down in the decree are sufficient to reduce the risk.

SECTION3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
Sulphuric acid 36 % Note: B	>= 14 <= 20%	Skin Corr. 1A, H314	016-020-00-8	7664-93-9	231-639-5	01-2119458 838-20

SECTION4. First aid measures

4.1. Description of first aid measures

Inhalation:

Air the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product):

Take contaminated clothing Immediately off.

In case of contact with skin, wash immediately with water.

Consult a physician immediately

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

Drink water with egg white; do not give bicarbonate.
Absolutely do not induce vomiting or emesis. Seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a doctor if symptoms persist

SECTION 5. Firefighting measures**5.1. Extinguishing media**

Advised extinguishing agents:

Water spray, CO₂, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing means to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

5.2. Special hazards arising from the substance or mixture

No data available.

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective suit.

The spray water can be used to protect the people involved in the extinction

You may also use self-respirator, especially when working in confined and poorly ventilated area and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)

Keep containers cool with water spray

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provision of sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spill with earth or sand.

If the product has entered a watercourse in sewers or has contaminated soil or vegetation, notify it to the authorities.

Discharge the remains in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 For containment:

Rapidly recover the product, wear a mask and protective clothing

Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material.

Prevent it from entering the sewer system.

6.3.2 For cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid contact and inhalation of vapors
Wear protective gloves protective clothing eye protection face protection.
In residential areas do not use on large surfaces.
At work do not eat or drink.
See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabeled containers.
Keep containers upright and safe by avoiding the possibility of falls or collisions.
Store in a cool place, away from sources of heat and direct exposure of sunlight.

7.3. Specific end use(s)

Professional use:
Photographic and cinematographic treatment

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Related to contained substances:
Sulphuric acid 36 %:
Directive 2009/161/EU:
limit values (8 hours) = 0.05 mg/m³
Monitoring procedures: refer to Legislative Decree 81/08.
- Substance: Sulphuric acid 36 %
DNEL
Local effects Long term Workers inhalation = 0,05
Local effects Short term Workers inhalation = 0,1 (mg/m³)
PNEC
Sweet water = 0,0025 (mg/l)
Sea water = 0,00025 (mg/l)
sediment Sea water = 0,002 (mg/kg/sediment)

8.2. Exposure controls

Appropriate engineering controls:

Professional use:

Not established

Individual protection measures:

(a) Eye / face protection

Wear mask

(b) Skin protection

(i) Hand protection

When handling the pure product use chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3)

(ii) Other

When handling the pure product wear full protective skin clothing.

(c) Respiratory protection

Use adequate protective respiratory equipment (EN 14387:2008)

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Related to contained substances:

Sulphuric acid 36 %:

Do not let this chemical contaminates the environment.

SECTION9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical and chemical properties	Value	Determination method
Appearance	Liquid	
Odour	undefined	
Odour threshold	undefined	
pH	< 0.50	pH METRO
Melting point/freezing point	Not determined	
Initial boiling point and boiling range	< 125 °C	
Flash point	non flammable	ASTM D92
Evaporation rate	Irrilevant	
Flammability (solid, gas)	Irrilevant	
Upper/lower flammability or explosive limits	Irrilevant	
Vapour pressure	Irrilevant	
Vapour density	Irrilevant	
Relative density	1.270 ± 0.010 a 25 °C	
Solubility	in water	
Water solubility	Complete	
Partition coefficient: n-octanol/water	Irrilevant	
Auto-ignition temperature	Irrilevant	
Decomposition temperature	Irrilevant	
Viscosity	Irrilevant	
Explosive properties	not explosive	
Oxidising properties	Oxidizer	

9.2. Other information

No data available.

SECTION10. Stability and reactivity**10.1. Reactivity**

Related to contained substances:

Sulphuric acid 36 %:

If you add the acid dilution water, never the reverse. Reacts violently with water.

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

Nothing to report

10.5. Incompatible materials

It can generate toxic gases to contact with acids, amide, aliphatic and aromatic amines, carbamate, halogenated substances, isocyanetic, organic sulfide, nitrile, organic phosphates, inorganic sulfide, polymerizable compounds. It can be easy ignite in contact with other substances.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**

ATE(mix) oral = ∞

ATE(mix) dermal = ∞

ATE(mix) inhal = ∞

- (a) acute toxicity: based on available data, the classification criteria are not met.
- (b) skin corrosion/irritation Corrosive product: causes severe skin burns and eye damage.
- (c) serious eye damage/irritation: Corrosive product: causes severe skin burns and eye damage. - If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.
- (d) respiratory or skin sensitization: based on available data, the classification criteria are not met.
- (e) germ cell mutagenicity: based on available data, the classification criteria are not met.
- (f) carcinogenicity: based on available data, the classification criteria are not met.
- (g) reproductive toxicity: based on available data, the classification criteria are not met.
- (h) specific target organ toxicity (STOT) single exposure: based on available data, the classification criteria are not met.
- (i) specific target organ toxicity (STOT) repeated exposure based on available data, the classification criteria are not met.
- (j) aspiration hazard: based on available data, the classification criteria are not met.

B/W KIT INVERSIONE SBIANCA Permanganato PARTE B LT 1:

LD50 (rat) Oral (mg/kg body weight) = 5000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 1

Related to contained substances:

Sulphuric acid 36 %:

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE.

Acute oral toxicity (LD50): 2140 mg/kg [Rat.].

Acute toxicity of the vapor (LC50): 320 mg/m³ 2 hours [Mouse].

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified 1 (Proven for human.) by IARC, + (Proven.) by OSHA. Classified A2 (Suspected for human.) by ACGIH.

May cause damage to the following organs: kidneys, lungs, heart, cardiovascular system, upper respiratory tract, eyes, teeth.

Other Toxic Effects on Humans:

Extremely hazardous in case of inhalation (lung corrosive).

Very hazardous in case of skin contact (corrosive, irritant, permeator), of eye contact (corrosive), of ingestion, .

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

Mutagenicity: Cytogenetic Analysis: Hamster, ovary = 4mmol/L

Reproductive effects: May cause adverse reproductive effects based on animal data. Developmental abnormalities (musculoskeletal) in rabbits at a dose of 20 mg/m³ for 7 hrs.(RTECS)

Teratogenicity: neither embryotoxic, fetotoxic, nor teratogenic in mice or rabbits at inhaled doses producing some maternal toxicity

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects:

Skin: Causes severe skin irritation and burns. Continued contact can cause tissue necrosis.

Eye: Causes severe eye irritation and burns. May cause irreversible eye injury.

Ingestion: Harmful if swallowed. May cause permanent damage to the digestive tract. Causes gastrointestinal tract burns. May cause perforation of the stomach, GI bleeding, edema of the glottis, necrosis and scarring, and sudden circulatory collapse(similar to acute inhalation). It may also cause systemic toxicity with acidosis.

Inhalation: May cause severe irritation of the respiratory tract and mucous membranes with sore throat, coughing, shortness of breath, and delayed lung edema. Causes chemical burns to the respiratory tract. Inhalation may be fatal as a result of spasm, inflammation, edema of the larynx and bronchi, chemical pneumonitis, and pulmonary edema. Cause corrosive action on mucous membranes. May affect cardiovascular system (hypotension, depressed cardiac output, bradycardia). Circulatory collapse with clammy skin, weak and rapid pulse, shallow respiration, and scanty urine may follow. Circulatory shock is often the immediate cause of death. May also affect teeth(changes in teeth and supporting structures - erosion, discoloration).

Chronic Potential Health Effects:

Inhalation: Prolonged or repeated inhalation may affect behavior (muscle contraction or spasticity), urinary system (kidney damage), and cardiovascular system, heart (ischemic heart leisons), and respiratory system/lungs(pulmonary edema, lung damage), teeth (dental discoloration, erosion).

Skin: Prolonged or repeated skin contact may cause dermatitis, an allergic skin reaction.

LD50 (rat) Oral (mg/kg body weight) = 5000

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) = 1

SECTION12. Ecological information

12.1. Toxicity

Related to contained substances:

Sulphuric acid 36 %:

Desmodesmus subspicatus algae growth inhibition: EC50 72h> 100 mg / l)

Fish freshwater Short term: Bluegill LC50 96h:> 16 - <28 mg / l)

Freshwater fish Long Term: Salvelinus fontinalis NOEC: 0.31 mg / l

Freshwater fish Long Term: Jordanella floridae NOEC (65d): 0.025 mg / l

Activated sludge in freshwater NOEC (37 d): ca. 26 g / l "weight of vidence"

Invertebrates Daphnia magna Short term: EL50 48 / hours:> 100 mg / l

Invertebrates Tanytarsus dissimilis Long Term: NOEC: 0.15 mg / l

Use according to good working practices to avoid pollution into the environment.

12.2. Persistence and degradability

Related to contained substances:

Sulphuric acid 36 %:

Degradabilit: abiotic hydrolyzes the product

Biotic: Degradabilit not required as inorganic compound.

12.3. Bioaccumulative potential

Related to contained substances:

Sulphuric acid 36 %:

No data available

12.4. Mobility in soil

Related to contained substances:

Sulphuric acid 36 %:

Is not adsorbed by soil particles.

12.5. Results of PBT and vPvB assessment

The substance / mixture NOT contains substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

12.6. Other adverse effects

No adverse effects

SECTION13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

SECTION 14. Transport information**14.1. UN number**

ADR/RID/IMDG/ICAO-IATA: 2796

ADR exemption because compliance with the following characteristics:

Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packagings placed in shrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg

**14.2. UN proper shipping name**

ADR/RID/IMDG: ACIDO SOLFORICO non contenente più del 51% di acido o ELETTROLITA ACIDO PER ACCUMULATORI

ADR/RID/IMDG: SULPHURIC ACID with not more than 51% acid or BATTERY FLUID, ACID

ICAO-IATA: SULPHURIC ACID with not more than 51% acid or BATTERY FLUID, ACID

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class : 8

ADR/RID/IMDG/ICAO-IATA: Label : Limited quantities

ADR: Tunnel restriction code : E

ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L

IMDG - EmS : F-A, S-B

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: II

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is not environmentally hazardous

IMDG: Marine polluting agent : Not

14.6. Special precautions for user

The transport must be carried out by authorised vehicles carrying dangerous goods in accordance with the requirements of the current edition of the agreement A.D.R. applicable national provisions.

The transport must be carried out in the original packaging and in packages that are made from materials resistant to the content and not likely to generate with this dangerous reactions. Employees to the loading and unloading of dangerous goods have received proper training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

It is not intended to carry bulk

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Legislative Decree. 02/03/1997 n. 52 (Classification, packaging and labeling of dangerous substances). Legislative Decree 14/03/2003 n. 65 (Classification, packaging and labeling of dangerous substances). Legislative Decree. 02/02/2002 n. 25 (Risks related to chemical agents at work). D.M. 26/02/2004 Work (Exposure Limits Professional); D.M. 03/04/2007 (Implementation of Directive n. 2006/8 / EC). Regulation (EC) No. 1907/2006 (REACH), Regulation (EC) No. 1272/2008 (CLP), Regulation (EC) 790 / 2009.D.Lgs. September 21, 2005 n. 238 (Seveso Ter).

REGULATION (EU) No 1357/2014 - waste:

HP8 - Corrosive

15.2. Chemical safety assessment

The supplier has made an assessment of chemical safety

SECTION 16. Other information

16.1. Other information

Description of the hazard statements exposed to point 3

H314 = Causes severe skin burns and eye damage.

Classification based on data of all mixture components

Main normative references:

Directive 1999/45/EC

Directive 2001/60/EC

Regulation 1272/2008/EC

Regulation 2010/453/EC

Regolamento 529/2012 and subsequent updates

This data sheet cancels and replaces any previous edition.
